Your best practice evolving!









Macrofan HS Autolevel Primer

2K polyacrylic high solid self-levelling primer/filler (VOC<540 g/lt),

- Usable as a primer with direct adhesion in wet-on-wet systems
 - Suitable as a sealer in dry-on-dry systems
 - Suitable as a primer for plastics.

A true multipurpose innovation for all repair processes, where the painting process's maximum efficiency and quality is required.

Available in the following colours:



It allows you to match a full grey spectrum, thus attaining and optimising the finishes' covering power.

Main characteristics

- · Adhesion on the main original metal substrates with cataphoresis, also without sanding.
- · Overcoatable up to 5 days without sanding.
- · Satin/mat homogeneous aesthetical aspect as of the original fillers.
- Good flow and rapidity of w/w painting systems with water-borne HYDROFAN finishes and solvent-based MACROFAN finishes.
- · Good sanding in dry-on-dry systems.
- Adhesion on plastics used in the car field.
 On the plastic primer's black version it is possible to avoid any overcoating.

Main benefits

- ·It avoids preparation of intermediate phases (application of specific primers).
- · Reduction of process/application times and of sanding steps.
- · Greater flexibility in work scheduling (application of more parts at the same time).
- · Higher efficiency and productivity of the paint shop.
- · Energy consumption reduction.
- · Unaltered aesthetical aspect compared to D/D systems.
- Product consumption reduction through the choice of the most suitable primer/filler colour, with covering power optimisation.
- Stock reduction and the cutting down of errors due to wrong product/hardener use.

